

# **Declaration of Performance (DoP)**



According to Construction Products Regulation (EU) No 305/2011 Declaration number: **PFD-CPR-0031** 

1. Unique identification code of the product-type:

### 6000PLUS/OPHT/SL

2. Identification of the construction product as required under Article 11(4) of the CPR:

Analogue addressable multi-sensor with sounder, short circuit isolator and visual alarm

3. Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:

Fire detection and fire alarm systems for use in and around buildings

4. Name and address of the manufacturer as required under Article 11(5):

Protec Fire Detection plc, Protec House, Churchill Way, Nelson, Lancashire, BB9 6RT, ENGLAND

Telephone number: + 44 (0)1282 717171 Fax number: +44 (0)1282 717273

Web: www.protec.co.uk

5. Name and contact address of authorized representative whose mandate covers the tasks specified in Article 12(2)

Alan Palmer – Group Conformity Manager (address as above)

6. System of assessment and verification of constancy of performance of the construction product as set out in Annex V:

### System 1

7. In case of the declaration of performance concerning a construction product covered by a harmonized standard:

Notified Body: BRE, Bucknalls Lane, Watford, England WD25 9XX Telephone: +44 01923 664000 Notified Body number: 0832

nerformed the type testing and initial inspection of the manufacturing plant and of factory production control

performed the type testing and initial inspection of the manufacturing plant and of factory production control with continuous surveillance, assessment and evaluation of factory production control under system 1 and issued the following EC certificate of conformity: 0832-CPD-1172

8. In the case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued: (Not applicable, see item 7)

# **Declaration of Performance (DoP)**

## 9. Declared performance:

All requirements including the Essential Characteristics and the corresponding performances for the intended use or uses indicated in (3), above have been determined as described in the harmonised European standard(s) (hEN) mentioned in the following table.

Essential characteristics	Performance	Harmonised tech	nical specification (hEN)
Performance under fire	Pass	4.2, 4.3. 5.2, 5.3,	EN 54-3:2001 + A1: 2002
condition			
Operational reliability	Pass	4.4, 4.5, 4.6, 5.4,	EN 54-3:2001 + A1: 2002
Durability of operational			EN 54-3:2001 + A1: 2002
reliability, temperature	Pass	5.5, 5.7, 5.8, 5.9	
resistance			
Durability of operational	Pass	5.8, 5.9,	EN 54-3:2001 + A1: 2002
reliability, humidity resistance			
Durability of operational	Pass	5.11	EN 54-3:2001 + A1: 2002
reliability, corrosion resistance			EN 54 0 0004 A4 0000
Durability of operational		5401 545	EN 54-3:2001 + A1: 2002
reliability, shock and vibration	Pass	5.12 to 5.15	
resistance			
Durability of operational	Pass	5.16	EN 54-3:2001 + A1: 2002
reliability, electrical stability	1 3.00		FN 54 0 0004 A4 0000
Durability of operational	Pass	5.17	EN 54-3:2001 + A1: 2002
reliability, resistance to ingress			
Operational reliability	Pass	4.2, 4.3, 5.2 to 5.6, 5.8 6.1, 6.2	EN 54-5:2000 + A1: 2002
Tolerance to supply voltage	Pass	4.4 to 4.11	EN 54-5:2000 + A1: 2002
Durability of operational	Pass		EN 54-5:2000 + A1: 2002
reliability and response delay,		5.7	
temperature resistance	_		
Durability of operational	Pass	5.9, 5.10	EN 54-5:2000 + A1: 2002
reliability, vibration resistance	_	3.5, 3.13	
Durability of operational	Pass	5.14, 5.12	EN 54-5:2000 + A1: 2002
reliability, humidity resistance	_	5.1., 5.1.2	
Durability of operational	Pass	5.13	EN 54-5:2000 + A1: 2002
reliability, corrosion resistance	_	3	
Durability of operational	Pass	5.18	EN 54-5:2000 + A1: 2002
reliability, electrical stability			
Nominal activation			
condition/sensitivity response			EN 54 7 0000 A4 0000
delay (response time) and	Pass	4.8, 5.2, 5.3, 5.4, 5.6, 5.7, 5.18	EN 54-7:2000 + A1: 2002
performance under fire			
condition	D.	401 47 401 444	EN 54 7 0000 A4 0000
Operational reliability	Pass	4.2 to 4.7, 4.9 to 4.11	EN 54-7:2000 + A1: 2002
Tolerance to supply voltage	Pass	5.5	FN 54 7 0000 A4 0000
Durability of operational	Dana	50.50	EN 54-7:2000 + A1: 2002
reliability and response delay,	Pass	5.8, 5.9	
temperature resistance		<u> </u>	FN 54 7-0000 A4: 0000
Durability of operational	Pass	5.13, 5.16	EN 54-7:2000 + A1: 2002
reliability, vibration resistance		<u> </u>	FN 54 7 0000 A4 0000
Durability of operational	Pass	5.10, 5.11	EN 54-7:2000 + A1: 2002
reliability, humidity resistance		<u> </u>	EN 54.7.0000 A4. 0000
Durability of operational	Pass	5.12	EN 54-7:2000 + A1: 2002
reliability, corrosion resistance		-	EN 54 7:0000 Ad 0000
Durability of operational	Pass	5.17	EN 54-7:2000 + A1: 2002
reliability, electrical stability			

Performance under fire conditions	Pass	5.2	EN 54-17:2005
Operational reliability	Pass	4	EN 54-17:2005
Durability of operational	Pass		EN 54-17:2005
reliability, temperature resistance		5.4, 5.5	
Durability of operational reliability, vibration resistance	Pass	5.9 to 5.12	EN 54-17:20055
Durability of operational reliability, humidity resistance	Pass	5.6, 5.7	EN 54-17:2005
Durability of operational reliability, corrosion resistance	Pass	5.8	EN 54-17:2005
Durability of operational reliability, electrical stability	Pass	5.3, 5.13	EN 54-17:2005

10. The performance of the product indentified in (1) and (2), is in conformity with the declared performance in (9). This declaration of performance is issued under the sole responsibility of the manufacturer indentified in (4)

# **Declaration of Conformity**

This Declaration of Performance also serves as a **CE Declaration of Conformity** for the product regarding the following additional European Directives:

• Electromagnetic Compatibility Regulation 2006 SI No.2006/3148. (which implements the Council Directive 2004/108/EC "the EMC Directive")

European Harmonised standards (hEN):

EN 50130-4:2011 (immunity tests in conjunction with external type testing)
EN 61000-4:2007/A1:2011 (emission tests, self-declared through arranged tests)

• **Electrical Equipment (Safety) Regulation** 1994 SI 3260 (which implements Council Directive 2006/95/EC the "Low Voltage Directive"):

European Harmonised standard (hEN): EN 60950-1:2006/A11:2009

• The Restriction of the Use of Certain Hazardous Substances in Electrical and Electronic Equipment Regulations 2012

No. 3032 (which implements Council Directive 2011/65/EU the "RoHS2 Directive"):

I hereby declare that the equipment named above has been designed to comply with the relevant sections of the above referenced specifications. The named product complies with all applicable Essential Requirements of the Directives.

Signed for and on behalf of the manufacturer:

Name: Dr Fariz Khellaf

**Position: Technical Director** 

Khellafferiz

Protec Fire Detection PLC, Lomeshaye Industrial Estate, Churchill Way, Nelson. Lancashire. England, BB9 6RT

